

Saratoga Effetto Intonaco – Plaster Effect Acrylic Sealant

Saratoga Effetto Intonaco – Plaster Effect Acrylic Sealant is an acrylic one-component sealant, specially formulated to reproduce civil plaster effect, that is thin mortar one.

Saratoga Effetto Intonaco – Plaster Effect Acrylic Sealant has excellent adhesion to porous materials, even if temporarily wet.

Saratoga Effetto Intonaco – Plaster Effect Acrylic Sealant can be painted with the most common house paints or enamels, for internals or externals.

Saratoga Effetto Intonaco – Plaster Effect Acrylic Sealant has excellent resistance to atmospheric agents.

APPLICATION FIELDS

Saratoga Effetto Intonaco – Plaster Effect Acrylic Sealant is used to fill cracks, fissures and holes in façades, walls and ceilings, for connection joints between wall and doors and windows frames.

APPLICATION

All surfaces must be clean, dust free and degreased.

- Remove all possible parts that do not adhere.
 - It is recommended to use a masking tape on both sides of the joint for a better result (remove right after application).
 - Cut the nozzle at the desired diameter.
 - Apply using a standard sealant gun or a compressed air one.
 - Apply at the bottom of the gap some insulation material (such as adhesive tape); with deep gaps, fill with some fill-up material (such as Saratoga Joint-Filler or expanded plastic).
 - Protect from rain and water in general right after application, for 2 hours in a warm environment, or 24 hours in a cold one.
- Right after use, clean with water. When cured, clean with a cutter.

Specific data

Specific weight		1,76
Consistency		Thixotropic
Extrusion rate	g/min.	100-120
Working time	minutes*	10-15
Cure time	weeks*	1-2
Application temperature	°C	+5 / + 40
Tensile strength	MPa	1,3
Modulus at 100% elongation	MPa	0,5
Elongation at break	%	150
Shore A hardness	°	35
Elastic recovery	%	>70
Working movement	%	6
Heat resistance	°C	-30 / +80

*At 23°C and 50% Relative Humidity

STORAGE AND SHELF LIFE

Between +20 and +25°C its shelf life is 24 months since manufacturing date. Avoid frost.

PRIMER

A primer is not needed on most common porous supports used in building industry. With very porous surfaces, it is recommended to treat beforehand with Effetto Intonaco – Plaster Effect Acrylic Sealant diluted with water in proportion of: 1 part of sealant to 2 parts of water.

LIMITATIONS

Do not use on:

- Non-varnished metal surfaces.
 - Joints constantly submerged in water.
 - Joints with an above 6% working movement.
- In case, use Saratoga Neutral Silicone Sealant.

CAUTIONS

Keep out of the reach of children.

Consult Material Safety Data Sheet for full list of hazards and the directions on the product label itself.

For further information, please visit our site www.saratoga.it

Product Description	Pack size	Product code	Box quantity	EAN Code
Plaster Effect White	310 ml	85 201 001	15	8 005860 852013



06/2014, 5th Rev- The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings . All the information herein do not involve the assumption of responsibility in case of damages. Before using the product, the user should carry out any necessary test in order to ensure that the product is suitable for the intended application. All users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, for specific features, please contact Saratoga Int Sforza spa. Our specialists are at your disposal for further information.